

**VDOT-42SK\***

**SINGLE & DUAL ACTION PULL STATIONS**



Dual Action

▪ **Key Features**

- Single or Dual Action.
- Screw Terminal Connections.
- DC and AC Voltage Contact Ratings.
- Gold Plated Alarm Contacts.
- Surface or Weatherproof Back-box.

▪ **Specifications**

Listings	UL, ULC, FM, CSFM, MEA
Temperature	-40° to 150°F; 40° to 65°C, 90% relative humidity @ 100°F; 38°C
Switch rating	2 Amps @ 125 VDC, 2 Amps @ 240 VAC,
Screw Terminal Block	#22 to #14 gauge wire
Weight	1.2 lbs, 0.55 kg
Dimensions (Pull Station)	12.1 x 8.3 x 2.8 cm
Dimensions (Backboxes)	12.1 x 8.3 x 5.7 cm (Outside) 5.4 cm (Inside Depth)
Lock	CAT30 aka "B" keylock is standard
Break-Rod	Optional, not required for operation. One break-rod is included with each pull station

▪ **Description**

The VDOT-42SK\* Series are key-reset, manual pull stations designed to meet the requirements for many applications. They are constructed from a rugged, but lightweight, die-cast metal alloy for increased performance and longevity. This series of stations is available in single action (PULL lever) or dual action (PUSH bar and PULL lever) models.

Velocity VDOT Series pull stations include a terminal strip that can accommodate wiring from #22 to #14 AWG. Contacts are gold plated to minimize risk of corrosion. All models have been tested by UL and found in compliance with the pull force requirements of the Americans with Disabilities Act (ADA).

▪ **Operation**

The stations are operated by pulling the handle marked "PULL" on the front of the unit as far down as it will go. At that point, the handle will lock in place and is easily visible from up to 50 feet. The activation handle is reset by opening the station with the key, placing the "PULL" handle to its normal upright position and relocking the station. On the dual action, the "PUSH" bar moves inward allowing the "PULL" handle to be operated by a single hand.

▪ **Mounting Configurations**

The stations are operated by pulling the handle marked "PULL" on the front of the unit as far down as it will go. At that point, the handle will lock in place and is easily visible from up to 50 feet. The activation handle is reset by opening the station with the key, placing the "PULL" handle to its normal upright position and relocking the station. On the dual action, the "PUSH" bar moves inward allowing the "PULL" handle to be operated by a single hand.



Single Action

▪ **Product Codes**

Dual Action*	VDOT-42SK1
Single Action*	VDOT-42SK2
Indoor Back Box	VDOT-32S
Outdoor Back Box	VDOT-WP

All specifications are subject to change without any notice. For more information, contact with VELOCITY.



Zeta Alarms Limited  
72-78 Morfa Road, Swansea  
SA1 2EN  
Tel: +44 1792 455 175 FAX: +44 1792 455 176

**Distributed By**